

Charging Connector	SAE J1772 Type 1
Input Power - Standard	208/240VAC, Single Phase 32A
Installation Type	NEMA 6-50 Plug Included
Frequency	60Hz
Output Power	7.68kW (240VAC@32A)

### Material Specifications

Dimensions	11.14" x 7.56" x 3.11"
Enclosure Rating	NEMA 4
Impact Resistance	IK10
Charging Cable Length	25ft.
Mounting Type	Wall Mount Included
Holster for Connector	Click in Holster for J-1772

### Light Indicator

Green Steady	Ready
Green Flashing (fast)	Authorised, wait for EV Connect
Green Flashing (slow)	Suspend (occupying)
Blue Flashing (slow)	Charging
Red Steady	Unrecoverable Fault
Yellow Steady	Out of Service
Yellow Flashing (slow)	Booting / Firmware Upgrading

### Remark:

Fast Flash:	On Time 300ms, Off Time 200ms, 2Hz
Slow Flash:	On Time 1200ms, Off Time 800ms, 0.5Hz

### Environmental & Safety Specifications

Operating Temperature	-22F to +122F (-30C to +50C)
Storage Temperature	-40F to +158F (-40C to +70C)
Operating Humidity	95% RH Non-Condensing
Safety Compliance	UL Listed for USA UL 50/991/1449/1998/2231/2594

### WISE Household LIMITED WARRANTY

WISE warrants that this product shall be free of defects in materials and workmanship under normal household use for a period of two (2) years.